

VOIP PHONE SNOM 370

The Next Generation of VoIP Phones

Data Sheet

P/N: snom 370

snom
VoIP phones



- Tilttable high-definition graphical display (240X128 pixels)
- Call indication LED
- 47 keys, 13 LEDs
- 12 programmable function keys
- Speakerphone
- 2 x IEEE 802.3
10/100 Mbps switch
- Power over Ethernet
- Multiple audio device support
- Expansion module with 42 programmable function keys
- SIP RFC3261
- Security: SIPS/SRTP, TLS
- STUN, ENUM, NAT, ICE
- Codecs: G.711, G.729A, G.723.1, G.722, G.726, GSM 6.10 (full rate)



Usability

The snom 370 is the VoIP phone for the business user who needs immediate access to all of their important information.

With the large graphical, high-definition display, the snom 370 offers an improved and extended presentation of call lists, address books and caller information. Caller information can be customized easily through XML to depict the information the user wants displayed.

Through the mini browser, users can have direct access to their own applications via the display screen. Users can not only customize the design of the display but, also view news tickers and other information as well as access central or public phone



Security

directories. The large LED (red) announces incoming calls.

More flexibility and productivity for your everyday work life. The improved interface guarantees ease of use and comfort. Context-sensitive menus offer additional options according to individual requirements. The snom 370 supports several audio devices simultaneously, for example, it is possible to use the handset or headset and the loudspeaker concurrently.

More performance through expanded memory. The snom 370 offers more additional customer-oriented functionalities and applications. The expanded memory capacity enables the



Interoperability

depiction of graphics and high resolution pictures to show the status of contacts (e. g., busy, on-line, off-line) similar to Instant Messenger. It is also possible to play music and media files and to integrate applications like VPN for increased security.

Afraid of unwanted listeners, data theft or spam calls? To avoid problems with unwanted violations of your audio data, the snom 370 supports the security standards TLS (Transport Layer Security), SRTP, and SIPS which are necessary to protect against electronic eavesdropping and data theft.

TECHNICAL DATA SNOM 370

GENERAL FEATURES

- **Dimensions:**
approx. 25 x 20 x 13 cm
- **Weight:** approx. 960 g
- **Safety:** IEC 60950-1:2001,
CB Test Certificate: DE 008417
- **Certifications:** FCC Class B,
CE Mark
- **Power consumption:** 2.6-2.8
watts

CONNECTORS

- **1 x LAN, 1 x PC:** RJ45 (Ethernet)
- **Power:** 5 V DC
- **Ethernet:** 2 x IEEE
802.3 10/100 Mbps switch
- **Power over Ethernet:**
IEEE 802.3af, Class 1
- **Handset:** RJ11 connector
- **Headset:** RJ11 connector
- **Expansion Module:**
Proprietary snom connector

USER INTERFACE

- 240 x 128 pixels, tiltable grayscale
graphical display, backlight
- 47 keys, 12 programmable
function keys with LEDs
(54 with the expansion module)
- Caller indication LED
- Caller-ID (with picture display)
- Message waiting indication LED
- Address book (250 entries)
- Address book import/export
- Speed dialing
- Local dial plan
- Number guessing
- Lists of missed, received and dialed
calls (100 entries each)
- Call waiting indication
- Clock, daylight saving, call-timer
- Call blocking (deny list)
- Blocking of anonymous calls
- Handling of up 12 calls
simultaneously
- Menu-driven user interface
- Ring tone selection, import of
individual ring tones

- National language support for
selected languages (NLS)
- Do not disturb
- Speakerphone (full duplex)
- Auto answer mode
- Keyboard lock

CALL FEATURES

- Hold
- Blind transfer, attended transfer
- Music on hold support
(only via PBX)
- Divert
- Conferencing (3-way conference
bridge on phone)
- Call park, call pick-up (only via PBX)
- Call completion
- Client Matter Code (CMC)
- Call waiting/switching between calls
- Redialing
- RTP multicast paging
- Multiple audio device support

WEB SERVER

- Embedded web server HTTP/HTTPS
- Easy configuration of the phone,
remote configuration
- Dial from web interface
- Password protection
- Diagnostics (tracing, logging,
syslog)

SECURITY, QUALITY OF SERVICE

- HTTPS (server/client)
- Transport Layer Security (TLS)
- SRTP (RFC3711), SIPS
- RTCP
- VLAN (802.1 pq)

CODECS, AUDIO

- G.711 A-law, μ -law
- G.729A, G.723.1, G.727
- GSM 6.10 (full rate)
- G.722
- Comfort noise, voice activity
detection

SIP

- RFC3261 compliance
- UDP, TCP and TLS
- Digest/basic authentication
- Loose routing and strict routing
support
- PRACK (RFC3262)
- Error-information support
- Reliability of provisional responses
(RFC3262)
- Early media support
- DNS SRV (RFC3263),
redundant server support
- Offer/answer (RFC3264)
- Message Waiting Indication
(RFC3842), subscription for
MWI events (RFC3265)
- Dialog-state monitoring (RFC 4235)
- In-band DTM F/out-of- band DTM F/
SIP INFO DTMF
- STUN client (NAT traversal)
- ENUM (RFC3261), NAPTR
(RFC2915), rport (RFC3581),
REFER (RFC3515)
- Event list subscription support
(RFC4662)
- Bridged line appearance (BLA)
- Auto provisioning with PnP
- Presence/buddylist features
- Busy lamp field support (BLF)
- Presence publishing

INSTALLATION

- Automatic software update
- Automatic settings retrieval
via HTTP/HTTPS/TFTP
- Installation via web interface
- Static IP provisioning, DHCP
- NTP

Copyright © 2000 – 2007 snom technology AG. All rights reserved. snom is a registered trademark of snom technology AG and affiliates in Germany, USA and certain other countries and regions. Unless specified otherwise, all trademarks, in particular product names, in this document are legally protected trademarks of snom technology AG. Other trademarks or registered trademarks mentioned in this document are the property of their respective manufacturers or owners. Product specifications contained in this document are subject to change without notice.